

**DS-PS1-E-WB**  
**Wireless Outdoor Sounder**

- 433 MHz two-way wireless communication
- 3 years battery lifespan (triggered every two weeks and alerting 90 s for each triggering)
- AES-128 encryption
- Front and rear panel tamper-proof
- 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm
- Buzzer Decibel: 110 dB
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission
- IP65 protective level

## ▪ Specification

Electrical characteristics	
Battery type	Battery (default power supply method) or 12 VDC
Power supply	Battery (default power supply method) or 12 VDC
Operation humidity	10% to 90% (no condensing)
Operation temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Battery lifespan	Up to 3 years (standby time)
Wireless transmission	
RF frequency	433 MHz
RF modulation	2GFSK
RF distance	900 m (open area)
General	
IP rate	IP65
Installation method	Wall mounting
Dimension(WxHxD)	190 × 200 × 47.3 mm(7.48" × 7.87" × 1.86" )
Shell material	PC+ABS
Weight	606.5 g (21.4 oz)

## ▪ Available Model

DS-PS1-E-WB

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

